

FP-1200



■ FP-1200

Product Code: 10147

Product Description: FirePro Fire Extinguishing Generator FP-1200

Features:

- LPCB, UL, KIWA, MED & BSI Certified
- Carbon-Steel casing Red-coated

■ FP-1200S

Product Code: 10395

Product Description: FirePro Fire Extinguishing Generator FP-1200S

Features:

- LPCB, UL, KIWA, MED & BSI Certified
- Stainless steel casing

■ FP-1200T

Product Code: 10316

Product Description: FirePro Fire Extinguishing Generator FP-1200T

Features:

- LPCB, UL, KIWA & BSI Certified
- This model can be activated by a Bulb Thermal Activator
- Carbon-Steel casing Red-coated

■ FP-1200TS

Product Code: 10622

Product Description: FirePro Fire Extinguishing Generator FP-1200TS

Features:

- LPCB, UL, KIWA & BSI Certified
- This model can be activated by a Bulb Thermal Activator
- Stainless steel casing

TECHNICAL INFORMATION

Model	FP-1200 / FP-1200S / FP-1200T / FP-1200TS
Activation method	Thermal (FP-1200T/ FP-1200TS) Electrical (Minimum pulse voltage: 1.5 VDC, Minimum pulse current: 0.8 A, Minimum pulse duration: 0.5 s)
Activator type	Heating element with 2.2 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	10900 g (excluding bracket)
Mass of FPC compound	1200 g
Operational discharge time	10 - 15 seconds
Dimensions	216 mm x 300 mm x 167 mm
Fire class	EN 2: A,B,C,F / NFPA 10: A,B,C

Generators are provided complete with brackets