

FP-5700



■ FP-5700

Product Code: 10151

Product Description: FirePro Fire Extinguishing Generator FP-5700

Features:

- LPCB, UL, KIWA, MED & BSI Certified
- Carbon-Steel casing Red-coated

■ FP-5700T

Product Code: 10319

Product Description: FirePro Fire Extinguishing Generator FP-5700T

Features:

- LPCB, UL, KIWA & BSI Approved
- This model can be activated by a Bulb Thermal Activator
- Carbon-Steel casing Red-coated

■ FP-5700S

Product Code: 10394

Product Description: FirePro Fire Extinguishing Generator FP-5700S

Features:

- LPCB, UL, KIWA, MED & BSI Certified
- Stainless steel casing

■ FP-5700TS

Product Code: 10625

Product Description: FirePro Fire Extinguishing Generator FP-5700TS

Features:

- LPCB, UL, KIWA & BSI Approved
- This model can be activated by a Bulb Thermal Activator
- Stainless steel casing

TECHNICAL INFORMATION

| | |
|---------------------------------------|--|
| Model | FP-5700 / FP-5700S / FP-5700T / FP-5700TS |
| Activation method | Thermal(FP-5700T/ FP-5700TS) Electrical (Minimum pulse voltage: 1.5 VDC, Minimum pulse current: 0.8 A, Minimum pulse duration: 0.5 s) |
| Activator type | Heating element with 2.2 ohm resistance |
| Current intensity to be tested | Maximum 5 mA |
| Weight (gross) | 26400 g (excluding bracket) |
| Mass of FPC compound | 5700 g |
| Operational discharge time | 15 - 20 seconds |
| Dimensions | 300 mm x 300 mm x 300 mm |
| Fire class | EN 2: A,B,C,F / NFPA 10: A,B,C |

Generators are provided complete with brackets