



**Model:** AF-X Fireblocker n-CM

**Article:** 10-15-150-03-02

#### GENERAL TECHNICAL INFORMATION

<b>fire classes</b>	A & B
<b>activation mechanism</b>	heating element 1.3 - 3.2 Ohm resistance
<b>activation current</b>	electric (6-36V D/C 1.0 A for 1-2 sec)
<b>test recording current</b>	max 40 mA (0.04 A) within 5 min

#### SPECIFICATIONS

<b>gross weight</b>	3.5 kg
<b>weight extinguishing agent</b>	450 g
<b>discharge time</b>	<60 sec
<b>discharge openings</b>	1
<b>max. installation height</b>	1.5 m
<b>discharge length</b>	1.5 m
<b>dimensions (h x diameter)</b>	45 x 9,4 cm
<b>outflow temperature 75°C</b>	<150 cm
<b>outflow temperature 200°C</b>	0 cm

#### PROTECTIVE REACH CONFORM ISO, EN & UL NORM

<b>EN 2 Class of fire</b>	<b>net m<sup>3</sup></b>
A	7.2

Please note; In the design of the system one should always add a safety factor of 30%.  
Please always use our Calculation Sheets for calculating the amount of aerosol.

#### EXAMPLES OF APPLICATION AREAS

<b>rooms</b>	ceiling floors
<b>engine compartments</b>	car bus train boat
<b>large switch rooms</b>	transformers control units cupboards